



MARMOPACO

1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Decorative natural stucco paste, formulated following the experience of ancient recipes, technically updated to market needs, which allows to obtain highly opaque and velvety finishes with a marble effect. Its enchanting opacity gives a particular depth to the walls and a seductive touch, of exclusive elegance and refinement, which remains absolutely balanced and never intrusive. Highly breathable, it has an exceptional good anti-mold power, thanks to the natural disinfectant power of lime. It hardens through a chemical carbonation process, calcium hydroxide (the primary binder of the product) which reacts with carbon dioxide in the air to form calcium carbonate which is the main component of marble, hence the name "marmorino". It is used as a high decoration finish in prestigious environments, both public and private.

2. COMPOSITION

Long seasoning putty lime, limestone filler with controlled grain size, non-toxic additives

3. METHOD OF APPLICATION

We recommend the application on lime substrates, but it can also be applied on gypsum or by-products, old water-based paints if strong and well anchored, after applying a coat of DERASOL H2O diluted with water in a 1 to 1 ratio, or Primer S for difficult surfaces difficult to adhere to (old washable paints, plasterboard, concrete, ceramics, etc.)

1. Spread a layer of MARMOPACO with a stainless steel trowel and level the support; if necessary repeat the operation with another layer.

2 Spread another layer of MARMOPACO taking care to obtain an absolutely smooth surface. As soon as the product tends to dry, exercise with a stainless steel trowel pressing it slightly in order to smoothen and compact the surface, thus obtaining the typical effect of this plaster.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 1,714 +/-5% Kg./Lt.

VISCOSITY: Thixotropic paste

DRYING to touch: 2 hours at 20°C.

DRYING Completely: 24 hours at 20°C.

APPLICATION TEMP: between 10°C and 30°C.

COVERAGE: 0,6 – 0,8 m²/Kg. (two coats)

COLOURS: From the colour

PACKAGE: Polyethylene drums Kg.20, Kg.4

TINTING: The colours can also be obtained through the tinting system: SPIVER Global Tinting System.

PRESERVATION: 24 months in the intact packages away from temperature changes.

HS-CODE: 32149000

5. ITEM OF SPECIFICATIONS

Decoration and protection of wall surfaces with matt marmorino effect plaster, of the MARMOPACO type of Spiver s.r.l., based on long seasoned slaked lime, limestone filler with controlled granulometry, non-toxic additives, light-resistant and alkali-resistant pigments, after suitable support treatment. Price including material and installation, excluding scaffolding per sq.M.

€

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it