



Rust Style



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Prestigious finishing of top class decoration for interiors and exteriors oxide effect .It allows you to obtain, with a very easy application, a unique result of extraordinary beauty. RUST STYLE is particularly suitable in typical modern environments, which require refined elegance, sites both in public places and private homes. RUST STYLE is highly suitable in exterior facades, which require special effect Corten steel, effect very trendy and very much appreciated by modern architecture. RUST STYLE is washable after about three weeks of application, non-flammable and provides good water vapour permeability.

2.COMPOSITION

Organic and Inorganic pigments, acrylic copolymer emulsion, special non-toxic additives. Free from harmful substances such as solvents and pigments containing lead and chrome.

3.METHOD OF APPLICATION

INTERNAL USE

Surface preparation.

Sandpaper, dust, cover any imperfections with STUCCOMURO, and apply a coat of FISSATIVO UNIVERSAL diluted with water in the ratio of 1: 5 to 1:10 depending on the surface absorption. Allow drying for at least 4 hours and applying two coats of PRIMER S tint Z-90, between each coat and the other minimum 4-5 hours.

Preparation of the compound

An additive of 70 ml. from ARTHE CONCENTRATE of the chosen colour, and in the case of the SILVER or GOLD colour add 250 ml. of ARTHE PEARL SILVER PEARL ARTHE or K-GOLD, in 2.5 Lt. of RUST STYLE, mix slowly and manually everything and the product will be ready to use (the compound has a poot-life of about 15 days)

Application

Apply RUST STYLE with a special DECORA' SPALTER, by making irregular movements on the surface, like crossed brushstrokes, wait about 20 minutes and start giving the first pressure with a stainless steel trowel on the surface. After about 10 minutes complete, with a stainless steel trowel, paying attention of repeating the same movements of the previous phase.

EXTERNAL USE

Surface preparation

The following surfaces are suitable; fine mortar made of lime and / or cement, mortar, painted and mineral or synthetic coatings, perfectly dry and cohesive. Do not apply on surfaces where there are signs of dampness or infiltration. Apply a coat of DERASOL H2O diluted in the ratio 1: 1 in water; after 12 hours, apply two coats of PRIMER S colour Z-90 diluted with 20-30% water.

Application

Apply RUST STYLE with a special DECORA' SPALTER, by making irregular movements on the surface, like crossed

brushstrokes, wait about 20 minutes and start giving the first pressure with a stainless steel trowel on the surface. After about 10 minutes complete, with a stainless steel trowel, paying attention of repeating the same movements of the previous phase.

Protection

Apply with roller or spray two layers, leaving a 24 hour interval between each application of TOP PROTECTOR, Transparent protective mat non-yellowing highly water repellent.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 1,020 kg/Lt +/-5%.

PACKAGE: Polyethylene containers Lt. 2.5.

MIXING RATIO: (for silver or gold) RUST STYLE Lt.2,5 and ARTHE PERLA ml.250.

VISCOSITY: Thixotropic aspect.

YIELD: About 10 m²/Lt.

APPLICATION TEMPERATURE: Between 8°C and 30°C.

FILM ASPECT: MATT (not shiny).

DILUTION: Ready to use (Do not dilute).

PACKAGE: Polyethylene containers Lt. 2.5.

DRYING: To dry 4-5h , incompletely 24-48h a 20°C

APPLICATION By brush, finishing touch with a stainless steel trowel.

PRESERVATION: 24 months in the intact packages, away from Temperature changes

5. ITEM OF SPECIFICATIONS

INTERNAL USE



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it



Rust Style



Decoration and protection of interior wall surfaces with decorative effect oxide, RUST STYLE Spiver Ltd. , Based on inorganic and organic pigments, acrylic copolymers in emulsion, special non-toxic additives, after suitable treatment of the surface with PRIMER Scolour indicated in the folder.

Price includes materials and implementation, excluding the scaffolding sqm.
€.....

EXTERNAL USE

Decoration and protection of exterior walls with decorative effect oxide, RUST STYLE Spiver Ltd. , Based on inorganic and organic pigments, acrylic copolymer emulsion, special non-toxic additives, after appropriate priming with consolidating fixative DERASOL H20, and subsequently treated with two coats of PRIMER S of the colour indicated, with a final top protection, with a transparent acrylic TOP PROTECTOR of Spiver Ltd.

Price includes materials and implementation, excluding the scaffolding sqm.
€.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product qual



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122
93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it

Scheda Tecnica: Rust Style SP105. Rev.1 La presente scheda annulla e sostituisce le precedenti